



[10191/955]

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant(s)

Joerg SCHAEFER, et al.

SERIAL NO.

09/238,262

FILED

January 27, 1999

TITLE

METHOD OF PRODUCING STRUCTURED

WAFERS

ART UNIT

1746

I hereby certify that this correspondence is being deposited with United States Postal Service as first class mail in an enveladdressed to: Assistant Commissioner for Pat nts, Washing

Anita K. Alanko **EXAMINER**

D.C. 20231, on

Assistant Commissioner for Patents

Washington, D.C. 20231

AMENDMENT TRANSMITTAL

SIR:

Please find transmitted herewith for filing in the above-identified patent application an Amendment.

No fee is believed to be required. However, if any fee is required, please charge to Deposit Account No. 11-0600. Similarly, please credit any overpayment into Deposit Account No. 11-0600. A duplicate copy of this transmittal letter is enclosed for that purpose.

Respectfully submitted,

KENYON & KENYON

Richard L. Mayer Reg. No. 22,490

One Broadway New York, NY 10004

(212) 425-7200

Dated: Nov. 16, 2000

NY01 322280 v 1



[10191/955]

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANTS:

Joerg SCHAEFER, et al

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class made in an onvelope addressed to: Assistant Commissioner for Patents, Washington,

D.C. 20231, on

SERIAL NO.:

09/238,262

Date_

FILED:

January 27, 1999

Signature /

TITLE.

METHOD OF PRODUCING STRUCTURED WAFERS

ART UNIT:

1746

EXAMINER:

Anita K. Alanko

Assistant Commissioner for Patents Washington, D.C. 20231

AMENDMENT

Sir:

In response to the Office Action dated August 16, 2000, please reconsider the above identified application based on the following:

IN THE CLAIMS:

Please amend the claims as follows:

4. (Amended) The method according to claim 3, further comprising the steps of:

applying a [thin] further passivation layer in the subareas, after the removal of the nitride layer in the subareas and before the wafer is etched; and

In the subareas and before the water is elened, and

completely removing the nitride layer.

5. (Amended) The method according to claim 2, wherein the photoresist technique <u>used</u> is

[an] a standard integrated circuit photoresist technique.